

Two printers in 1 for CAD/GIS medium workgroups⁽¹⁾







- Get the job done quickly without sacrificing quality thanks to this printer's fast (Economode) print setting-2 D/A1-sized prints per minute.
- Experience continuous printing with reliable HP 300-ml matte black ink cartridges, a convenient front-loading top roll, and media length tracking.
- Save time and paper with 2 online rolls with smart switching.
- Print batch HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, PowerPoint) files easily—without opening any application—thanks to the free HP Instant Printing Utility and the embedded Web
- Medium-sized teams can easily share this printer thanks to its built-in network card.



- Achieve rich, dark blacks and fine detailed lines with HP Vivera inks, including 2 HP Vivera blacks and a gray ink in this 6-ink printing system.
- Produce exacting detail with 0.0008 inch (0.02 mm) minimum line width, (2 and highly accurate drawings with 0.1% line accuracy.
- Easily create stunning large-format posters that convey your message loud and clear with the optional Serif PosterDesigner Pro for HP.(3
- Transform your everyday printing with 2 HP media innovations—new and improved HP

bond papers with ColorPRO Technology and HP Recycled Bond Paper, made of 100% recycled base paper.

 Optimize blueprints—use this printer's new printing mode for generic natural tracing

Print confidently with a reliable, secure solution

- A busy network is not a problem anymore thanks to 32 GB of memory for file processing and reliable In-printer processing architecture.
- Secure connectivity with built-in Gigabit Ethernet networking and secure IPsec and IPv6. A Linux PS driver offers additional support for Linux users.(4
- Trusted security—use advanced access controls via the embedded Web server; secure disk erase and the external hard disk accessory⁽⁵ provide even more security.
- Do more with your printer with PostScript capabilities.⁽⁴ And experience greater operating system support with original HP-GL/2 and RTL.
- Manage your printer fleet and costs with HP Web Jetadmin, embedded Web server and the HP accounting tool.



- Save paper with two roll configuration, print image nesting, blank print area detection, image auto-rotate and realistic print previews
- Less ink wasted thanks to efficient installation and maintenance routines
- Free, convenient cartridge and printhead recycling Supports 100% recycled HP media ENERGY STAR® Qualified Product





















- Improve your productivity with automatic switching among 2 rolls.
- HP-GL/2 addressable
- Serif PosterDesigner Pro for HP is an optional software accessory to be purchased separately.
- Available on the HP Designjet T1200 PostScript Version Printer only. Support in English.
- The 160 GB external hard disk drive accessory is an optional accessory to be purchased separately. This accessory is intended to replace the printer's internal hard disk as the repository of personal data, and can be removed from the

HP DESIGNJET T1200

PRINTER SERIES

TECHNICAL SPECIFICATIONS

	Fast: 28 sec/page on D/A1, 103 D/A1 prints per hour
Color images	Fast: 549 ft ² /hr (51 m ² /hr) ¹²
N 1 - 0	Best: 33.3 ft²/hr (3.1 m²/hr) ⁽³
Printing Print resolution	Up to 2400 x 1200 optimized dpi
Margins	Roll: 0.2 x 0.2 x 0.2 x 0.2 in (5 x 5 x 5 x 5 mm) (borderless on photo papers)
top x bottom x left x right)	Sheet: 0.2 x 0.67 x 0.2 x 0.2 in (5 x 16.75 x 5 x 5 mm)
Technology	HP Thermal Inkjet
nk types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
nk colors	Cyan, gray, magenta, matte black, photo black, yellow
nk drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
nk cartridge size	300 ml (matte black)
	130 ml (cyan, gray, magenta, matte black, photo black, yellow)
	69 ml (cyan, gray, magenta, photo black, yellow)
Printheads	3 (matte black and yellow, magenta and cyan, gray and photo black)
ine accuracy	+/- 0.1%/4
Minimum line width	0.0008 in (0.02 mm) (HP-GL/2 addressable)
Guaranteed minimum line width	0.0024 in (0.06 mm) (ISO/IEC 13660:2001(E)) ^{[5}
Maximum print length	300 ft (91 m) (OS and application dependent)
Media	, () (
Handling	Sheet feed; two automatic roll feeds; automatic roll-switching; automatic cutter
Types	Bond and coated papers, technical papers, films, photographic papers, backlit materials, self-adhesive materials
Weight	
	60 to 328 g/m²
Size	8.26 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) sheets
el . I	11 to 44 in (27.94 to 111.76 cm) rolls
Thickness	Up to 11.8 mil
Memory	
	32 GB dedicated file-processing memory, 160 GB hard disk ⁽⁷⁾
Connectivity	
nterfaces (standard)	1 Gigabit Ethernet (1000Base-T) port, 1 Hi-Speed USB 2.0 certified port, 1 EIO
	Jetdirect accessory slot
nterfaces (optional)	HP Jetdirect EIO print servers
Print languages (standard)	Base model: HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Tim languages (siandara)	PostScript Version Printer: Adobe® PostScript® 3™, Adobe PDF 1.7, TIFF, JPEG,
	HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Drivers (included)	HP-GL/2, HP-RTL, PostScript ⁶ drivers for Windows® (optimized for AutoCAD 2000 and
	higher); HP PCL 3 GUI, PostScript ⁶ drivers for Mac OS X and Linux ⁶ ; support for Citrix
	XenApp and Citrix XenServer environments
Recommended system requiremen	
Mac	Mac OS X v 10.4, Mac OS X v 10.5: PowerPC G4, G5, or Intel Core Processor; 1
	GB RAM; 2 GB available hard disk space
Windows	Windows XP® (SP2 or later): Intel® Pentium® family or AMD® K6/Athlon/Duron fami
	(1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista®: 32-bit (x86)
	or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	
Printer	69.7 x 28.4 x 41.3 in (1770 x 722 x 1050 mm)
Shipping	75.98 x 30.16 x 30.7 in (1930 x 766 x 778 mm)
Weight	
Printer	189 lb (86 kg)
	253 lb (115 kg)
Shipping	233 lb (113 kg)
Shipping What's in the box	
	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in
	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster,
What's in the box	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in
What's in the box Environmental ranges	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
What's in the box Environmental ranges Operating temperature	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C)
What's in the box Environmental ranges Operating temperature Recommended operating	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
Environmental ranges Operating temperature Recommended operating temperature	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	Printer, printheads (3 × 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A)
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Power consumption Maximum	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 4.4 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz),
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES),
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (IVC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar (VCCI); Certified as Class A product: Korea (KCC)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Off Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 4.4 B(A) 120 watts 4.7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, EUP, FEMP
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, standby Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic Environmental ENERGY STAR® qualified	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar (VCCI); Certified as Class A product: Korea (KCC)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Off Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 4.4 B(A) 120 watts 4.7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japar (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, EUP, FEMP

ORDERING INFORMATION

Product		
CH538A	HP Designjet T1200 44-in Printer	
CK834A	HP Designjet T1200 44-in PostScript Version Printer	
Accessories		
Q6709A	HP Designjet 44-inch Roll Feed Spindle	
CN501A	HP Designjet External Hard Disk	
J7961 G	HP Jetdirect 635n IPv6/IPsec Print Server	
CN088A	Serif PosterDesigner Pro for HP	
CN454A	SCP reprocontrol for HP (1 printer)	
CN455A	SCP reprocontrol for HP (2 printers)	
Original HP pri		
C9380A	HP 72 Gray and Photo Black Printhead	
C9383A	HP 72 Magenta and Cyan Printhead	
C9384A	HP 72 Matte Black and Yellow Printhead	
Original HP in	k cartridges	
C9397A	HP 72 69-ml Photo Black Ink Cartridge	
C9398A	HP 72 69-ml Cyan Ink Cartridge	
C9399A	HP 72 69-ml Magenta Ink Cartridge	
C9400A	HP 72 69-ml Yellow Ink Cartridge	
C9401A	HP 72 69-ml Gray Ink Cartridge	
C9403A	HP 72 130-ml Matte Black Ink Cartridge	
C9370A	HP 72 130-ml Photo Black Ink Cartridge	
C9371A	HP 72 130-ml Cyan Ink Cartridge	
C9372A	HP 72 130-ml Magenta Ink Cartridge	
C9373A	HP 72 130-ml Yellow Ink Cartridge	
C9374A	HP 72 130-ml Gray Ink Cartridge	
CH575A	HP 726 300-ml Matte Black Ink Cartridge	
	nting materials	
Q6627A	HP Super Heavyweight Plus Matte Paper 210 g/m², 36 in x 100 ft/914 mm x 30,5 m	
Q6628A	HP Super Heavyweight Plus Matte Paper 210 g/m², 42 in x 100 ft/1067 mm x 30,5 m	
C6030C	HP Heavyweight Coated Paper 130 g/m², 36 in x 100 ft/914 mm x 30,5 m	
C6569C	HP Heavyweight Coated Paper 130 g/m², 42 in x 100 ft/ 1067 mm x 30,5 m	
Q1956A	HP Heavyweight Coated Paper 130 g/m², 42 in x 100 ii/ 1007 min x 30,3 iii HP Heavyweight Coated Paper 130 g/m², 42 in x 225 ft/ 1067 mm x 67,5 m	
C6019B	HP Coated Paper 90 g/m², 24 in x 150 ft/610 mm x 45,7 m	
C6020B	HP Coated Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m	
C6980A	HP Coated Paper 90 g/m², 36 in x 300 ft/914 mm x 91,4 m	
C1860A	HP Bright White Inkjet Paper 90 g/m², 24 in x 150 ft/610 mm x 45,7 m now with ColorPRO Technology	
C1861 A	HP Bright White Inkjet Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology	
C6810A	HP Bright White Inkjet Paper 90 g/m², 36 in x 300 ft/914 mm x 91,4 m now with ColorPRO Technology	
Q1397A	HP Universal Bond Paper 80 g/m², 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology	
C3868A	HP Natural Tracing Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m	
C3875A		
51642B	HP Clear Film 174 g/m², 36 in x 75 ft/914 mm x 22,9 m HP Matte Film 160 g/m², 36 in x 125 ft/914 mm x 38,1 m	
Q1427A		
Q1421A	HP Universal High-gloss Photo Paper 190 g/m², 36 in x 100 ft/914 mm x 30,5 m HP Universal Semi-gloss Photo Paper 190 g/m², 36 in x 100 ft/914 mm x 30,5 m	
CG459A		
CG459A CG460A	HP Premium Matte Photo Paper 210 g/m², 24 in x 100 ft/610 mm x 30,5 m HP Premium Matte Photo Paper 210 g/m², 36 in x 100 ft/914 mm x 30,5 m	
C7960A	HP Reverse Print Matte Backlit Film 160 g/m², 36 in x 75 ft/914 mm x 22,9 m	
Q8834A	HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in x 75 ft/914 mm x 22,9 m	
CG886A		
	HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in x 100 ft/610 mm x 30,5 m	
CG887A CG888A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in x 100 ft/914 mm x 30,5 m	
	HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in x 100 ft/1067 mm x 30,5 m HP Cockle-free Coated Paper 100 g/m², 24 in x 150 ft/610 mm x 45,7 m	
CG883A		
CG884A	HP Cockle-free Coated Paper 100 g/m², 36 in x 150 ft/914 mm x 45,7 m	
CG885A	HP Cockle-free Coated Paper 100 g/m², 42 in x 150 ft/1067 mm x 45,7 m	
CG889A	HP Recycled Bond Paper 80 g/m², 24 in x 150 ft/610 mm x 45,7 m made of 100% recycled base paper	
CG890A	HP Recycled Bond Paper 80 g/m², 36 in x 150 ft/914 mm x 45,7 m made of 100% recycled base paper	
	CG891A HP Recycled Bond Paper 80 g/m², 42 in x 150 ft/1067 mm x 45,7 m made of 100% recycled base paper HP Care Pack Services	
US237E	HP 3-year Next Business Day Onsite Support	
H4518E	HP Installation Services with Network Setup	
US234E	HP 3 year Next Business Day Onsite Support (9x5)	
US230E	HP 3-year Next Business Day Onsite Support (13x5)	
US236E US235E	HP 4-year Next Business Day Onsite Support	
UJZJJL	HP 5-year Next Business Day Onsite Support	

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/designjet/supplies

- Mechanical printing time
 Printed on plain media with Economode on
 Printed on glossy media
 +/-0.1% of the specified vector length or +/-0.1 mm (whichever greater) at 73° F (23° C), 50-60% relative
 humidity, on E/AD printing material in Best or Normal mode with HP Mattle Film
 Measured on HP Mattle Film
 Collections that the LHP Decimals 11200 44 in Best Script Version Briston
- Only supported through the HP Designjet T1200 44-in PostScript Version Printer 384 MB RAM Memory

YOUR AUTHORIZED RESELLER



419.241.5157

www.newfaxcorp.com

FOR MORE INFORMATION, VISIT OUR WEBSITE AT WWW.HP.COM/GO/DESIGNJETT 1200

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe PostScript 3 is a trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AMD is a trademark of Advanced Micro Devices, Inc. Intel and Pentium are trademarks of Intel Corporation in the U.S. and other countries. Windows, Windows XP, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

